

MF6600



MailFinisher 6600 - In-Line with HP4515TN +1500 Sheet Tray. Includes In-Line Folder/Sealer, Vertical Stacker and Tray Management Cabinet System

System dimensions - H1100mm L1070mm closed 1300mm open W510mm allow an extra 400mm for printer trays to open

The MailFinisher 6600 system is a High volume In-Line System which is interfaced with a compatible laser printer, whereby the printer feeds the MF6600 directly and the forms are printed, folded and sealed in one single operation, therefore, speeding up the processing and also making it easier for the operator.

The MF6600 is provided with a Tray Management Cabinet System and High Capacity Vertical Stacker Output Unit as standard, providing a dedicated floor standing system with easy continuous unloading of up to 800 sealed forms in sequence.

The MF6600 incorporates lockable fold plates and an easy jam release system with easy access for the operator.

The system is only compatible with the following printers providing up to 2,500 sheet in-feed capacity (based on 80gsm paper).

HP LJ4250TN with additional 1,500 sheet paper tray
HP LJ4350TN with additional 1,500 sheet paper tray
HP LJ4515TN with additional 1,500 sheet paper tray #

The CF Print Rotation Card is not supported with this printer model.

A High Capacity Vertical Output Stacker is fitted as standard which holds up to 800 printed forms and also provides easy unloading whilst processing in sequence.

The MF6600 can also be used as an 'Offline' machine, where forms are processed through the machine by loading manually once the forms are printed separately (see PostMate6).

Please note the following:

- * The laser printer is not unique to this machine; it can still be used as a normal office laser.
- * The processing speed of the system is regulated by the page per minute of the printer.
- * 180 degrees print rotation **MUST** be specified to allow for the correct paper orientation to the sealer. This is a selectable option using the standard Windows driver. If you are not using a Windows driver and cannot rotate the print via your operating software, an optional CF card can be installed in the printer which will allow print rotation. For this card to operate correctly, the driver software must be PCL5e, as PCL6 is not supported. #
- * The system printer cannot be connected via parallel cable, only by USB or network cable.
- * All prices above exclude laser printer, although we are able to supply quotation if required.